

# Clean-Out

**A water-soluble cleaning agent for use in spray tanks and spray equipment**

**Ingredient:**

Cleaning Agents: 250 g/l

**SG (@20 °C) = 1,09 ± 0,02**

SEE CONTAINER FOR BATCH DETAILS  
COUNTRY OF ORIGIN: REPUBLIC OF SOUTH AFRICA  
VERSION 1.2: 05/2017

**agchem**   
formulating for tomorrow®  
**Rolfes**  
GROUP

Registered, Manufactured and Distributed by:  
Ag-Chem Africa (Pty) Ltd (Reg. No.  
1998/013411/07)  
P.O.Box 589, Silverton, 0127, Gauteng, RSA.  
Tel: (012) 803-0145 • Fax: (012) 803-8418  
[www.agchem.co.za](http://www.agchem.co.za)

- **Clean-Out** cleans spray tanks, nozzles and other spray equipment.
- **Clean-Out** removes dust, dirt and unwanted residues from spray tanks and containers.
- **Clean-Out** protects and cleans pumps and valves.
- **Clean-Out** reduces clogging of filters and nozzles.
- **Clean-Out** has no corrosive action on any metal components.
- **Clean-Out** will result in the alkaline hydrolysis of residues in the spray tank and nozzles.
- **Clean-Out** will cause foaming. Treated tanks and containers must all be thoroughly rinsed before re-use.
- **Clean-Out** may not be totally effective when used in extremely corroded spray tanks and equipment.

#### **DIRECTIONS FOR USE: Use only as indicated**

**20 mL per 10 L water**

**200 mL per 100 L water**

1. Dissolve the correct amount of **Clean-Out** in the specified volume of water.
2. Agitate thoroughly in the spray tank for at least 15 minutes.
3. Leave the solution overnight in the tank or container.
4. Open the valve in the spray tank or container and pump out the **Clean-Out** solution through the nozzles and spray hoses.
5. Refill the spray tank or container with clean water and circulate / agitate for at least 10 minutes.
6. Empty the container or spray tank completely through the boom, spray hoses and nozzles before re-use.

**Store at room temperature. Keep out of direct sunlight. Keep container closed when not in use.**